



MH241 and MH261 Series Industrial Barcode Printer

A Feature-Rich MH Family Beyond Your Expectations

The MH241/MH261 Series is TSC's mainstream industrial barcode label printer built upon the legacy of the MH240 Series. It brings new features to those looking for solutions to address evolving business challenges from growing production line demands to increasing operational complexities.

The MH241/MH261 Series is equipped with sophisticated TSC Sense Care supported by SOTI Connect and TSC Console remote printer management to monitor printer status and give warning messages to ensure maximum productivity and avoid downtime.

Capable of seamless connectivity, the MH241/MH261 Series is supported by both Apple-certified MFi Bluetooth 5.0 or 802.11a/b/g/n/ac Wi-Fi with Bluetooth 4.2 combo module that turns the barcode label printer into a connected network.

Key Features



Sophisticated TSC Sense Care

- Self-diagnostic TPH Care mechanism
- Nearreal-time information and updates for preventative actions
- Selectable media sensor settings



Dynamic Remote Printer Management

- Supports SOTI Connect through either Ethernet or Wi-Fi
- Powerful TSC Console for printer management



Multi-Connectivity

- GPIO: Supports common applicators and emulations
- Wi-Fi: Supports 802.11 a/b/g/n/ac and Bluetooth 4.2 combo module



Highly Adaptable

- Precise peel-off capability with 0.5" minimum label length (MH241 Series).
- Supports media width up to 6.8" (MH261 Series)
- Full mechanism for fine adjustment



Brilliant User Experience

- Media near end sensor detection
- Easy printhead and platen roller replacement

Applications



Manufacturing

- Industrial Printing
- Shipping/Receiving Labeling
- Warning/Caution Signage



Transportation and Logistics

- Pallet Labeling
- Distribution



Healthcare

- Pharmaceutical Labeling
- Asset Tracking

WILUX PRINT AG
Unterfeldstrasse 5
CH-8340 Hinwil

Tel.: +41 (0)55 253 24 24
Fax: +41 (0)55 253 24 25

mail@wilux.ch
www.wilux.ch
www.labellingshop.com



wilux print
swissness
Ihr Partner für Etikettier- und Kennzeichnungslösungen

MH241 and MH261 Series | Data Sheet

STANDARD			
Model	MH241	MH341	MH641
Resolution	8 dots/mm (203 DPI)	12dots/mm (300 DPI)	24 dots/mm (600 DPI)
Printing method	Thermal Transfer and Direct Thermal		
Max. print speed	356 mm (14")/second	305 mm (12")/second	152mm (6")/second
Max. print width	104 mm (4.09")		
Max. print length	25,400 mm (1000")	11,430mm (450")	2540 mm (100")
Enclosure	Die-cast print mechanism and base with bi-fold metal cover with large clear media view window		
Physical dimension	276 mm (W) x 326 mm (H) x 502 mm (D) 10.87" (W) x 12.83" (H) x 19.76" (D)		
Weight	15.60 kg (34.39 lbs)		
Label roll capacity	203.2 mm (8") O.D.		
Internal rewinder (full roll)	Internal rewinding kit (5" O.D.)(dealeroption)		
Ribbon	600 m long, max. O.D.90 mm, 1"core (ink coated outside or inside)		
Ribbon width	25.4 mm ~ 114.3mm (1"~ 4.5")		
Processor	32-bit RISCCPU		
Memory	<ul style="list-style-type: none"> •512MB Flash memory • 256MB SDRAM •microSD Flash memory card reader for Flash memory expansion, up to 32 GB 		
Interface	<ul style="list-style-type: none"> • RS-232 •USB 2.0 (High speed mode) •Internal Ethernet, 10/100 Mbps •USB host *2 (Front side), for scanner or PC keyboard •GPIO(DB15F)+ Centronics (factory option) •Internal Bluetooth 5.0 MFi(factory option) •Slot-in 802.11a/b/g/n/ac Wi-Fi with Bluetooth 4.2 combo module (dealer option) 		
Power	Internal switching power supply <ul style="list-style-type: none"> •Input: AC100-240V, 4-2A, 50-60Hz •Output: DC5V, 5A; DC24V, 7A; DC36V, 1.4A; Total 243W 		
LCD display/ Operation buttons	<ul style="list-style-type: none"> •6 operation buttons • 1LED (with 2 LEDs Green & Red) 		
LCD	3.5" color display, 320 x 240 pixel		
Sensors	<ul style="list-style-type: none"> •Gap transmissive sensor (position adjustable) •Black mark reflective sensor (Bottom or Top black mark sensor switchable and position adjustable) •Head open sensor •Ribbon encoder sensor •Ribbon end sensor 		
Real time clock	Standard		
Internal font	<ul style="list-style-type: none"> •8 alpha-numeric bitmap fonts •Monotype Image@true type font engine with CGTriumvirate Bold Condensed scalable font 		
Barcode	1Dbarcode Code 39, Code 93, Code128UCC,Code128subsets A.B.C,Codabar, Interleave 2 of 5, EAN-8, EAN-13,EAN-128,UPC-A, UPC-E, EAN and UPC2(5) digits add-on, MSI, PLESSEY, POSTNET, RSS-Stacked, GS1DataBar, Code 11,China Post 2Dbarcode PDF-417,Maxicode, DataMatrix, QRcode, Aztec		
Font & barcode rotation	0, 90, 180,270 degree		
Printer language	TSPL-EZD(Compatible to EPL, ZPL,ZPL II,DPL)		
Media type	Continuous,die-cut, black mark (Bottom side or top side black mark), fan-fold, notch, perforated, tag, care label (outside wound)		
Media width	20 ~ 114mm (0.79" ~ 4.5")		
Media thickness	0.06 ~ 0.28 mm (2.36 ~ 11mil)		
Media core diameter	3.81mm / 76.2mm (1.5"/3")		
Label length	5 ~ 25,400 mm (0.20" ~ 1,000")		
Environment condition	<ul style="list-style-type: none"> •Operation: 0 ~ 40 °C(32 ~ 104 °F),25~85% non-condensing •Storage: -40 ~ 60 °C(-40 ~ 140 °F),10~90% non-condensing 		
Safety regulation	FCCClass A, CEClass A, RCMClass A, UL, cUL, TÜV, CCC,KC,BIS, BSMI,EAC,Argentina S mark, Mexico CoC, ENERGY STAR®		
Environmental concern	Comply with RoHS,WEEE		
Accessories	<ul style="list-style-type: none"> •Windows labeling software CDdisk •Quick start guide •USB port cable •Power cord 		
RTC & Buzzer	Standard		
Limited warranty	<ul style="list-style-type: none"> •Printer: 2 years •Print head: 25 km (1 million inches) or 12 months which comes first •Platen: 50 km (2 million inches) or 12 months which comes first 		
Factory option	<ul style="list-style-type: none"> • GPIO(DB15F)+Parallel interface •Internal Bluetooth 5.0 MFi* 		
Dealer option	<ul style="list-style-type: none"> •Regular cutter (full cut guillotine cutter) •Heavy-duty cutter (full cut guillotine cutter) •Care label cutter •1" I.D. core media spindle 	<ul style="list-style-type: none"> •802.11a/b/g/n/ac Wi-Fi with Bluetooth 4.2 combo module (including slot-in housing)* •Peel-off kit •Internal rewinder kit (5" O.D.) 	
User option	<ul style="list-style-type: none"> •Basic cutter tray •Advanced cutter tray •Universal cutter tray •KP-200 Plus keyboard display unit 		



* Availability may vary by region.

MH241 and MH261 Series | Data Sheet

ADVANCED			
Model	MH241T	MH341T	MH641T
Resolution	8 dots/mm (203 DPI)	12dots/mm (300 DPI)	24 dots/mm (600 DPI)
Printing method	Thermal Transfer and Direct Thermal		
Max. print speed	356 mm (14")/second	305 mm (12")/second	152mm (6")/second
Max. print width	104mm (4.09")		
Max. print length	25,400 mm (1000")	11,430mm (450")	2540 mm (100")
Enclosure	Die-cast print mechanism and base with bi-fold metal cover with large clear media view window		
Physical dimension	276 mm (W) x 326 mm (H) x 502 mm (D) 10.87" (W) x 12.83" (H) x 19.76" (D)		
Weight	15.70 kg (34.61lbs)		
Label roll capacity	203.2 mm (8") O.D.		
Internal rewinder (full roll)	Internal rewinding kit (5" O.D.)(dealeroption)		
Ribbon	600 m long, max. O.D.90mm, 1"core (ink coated outside or inside)		
Ribbon width	25.4 mm ~ 114.3mm (1"~ 4.5")		
Processor	32-bit RISC CPU		
Memory	<ul style="list-style-type: none"> •512MB Flash memory •256MB SDRAM •microSD Flash memory card reader for Flashmemory expansion, up to 32 GB 		
Interface	<ul style="list-style-type: none"> •RS-232 •USB 2.0 (High speed mode) •Internal Ethernet, 10/100Mbps •USB host *2 (Front side), for scanner or PC keyboard •GPIO(DB15F)+Centronics (factory option) •Internal Bluetooth 5.0 MFi(factory option) •Slot-in 802.11a/b/g/n/ac Wi-Fi with Bluetooth 4.2 combo module(dealer option) 		
Power	Internal switching power supply <ul style="list-style-type: none"> •Input: AC100-240V, 4-2A, 50-60Hz •Output: DC5V, 5A; DC24V, 7A; DC36V, 1.4A;Total 243W 		
LCD display/ Operation buttons	<ul style="list-style-type: none"> •Multi-language selectable •6 operation buttons •1LED (with 2 LEDs Green & Red) 		
LCD	4.3" color display, 480 x 272 pixel; Resistive touch screen		
Sensors	<ul style="list-style-type: none"> •Gap transmissive sensor (position adjustable) •Black mark reflective sensor (Bottom or Top black mark sensor switchable and position adjustable) •Head open sensor •Ribbon encoder sensor •Ribbon end sensor •Media near end sensor 		
Real time clock	Standard		
Internal font	<ul style="list-style-type: none"> •8 alpha-numeric bitmap fonts •Monotype Image@true type font engine with CG Triumvirate Bold Condensed scalable font 		
Barcode	1D barcode Code 39, Code 93, Code128UCC, Code128subsets A,B,C, Codabar, Interleave 2 of 5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC2(5) digits add-on, MSI, PLESSEY, POSTNET, RSS-Stacked, GS1DataBar, Code 11, China Post 2D barcode PDF-417, Maxicode, DataMatrix, QRcode, Aztec		
Font & barcode rotation	0, 90, 180, 270 degree		
Printer language	TSPL-EZD(Compatible to EPL, ZPL, ZPL II, DPL)		
Media type	Continuous, die-cut, black mark (Bottom side or top side black mark), fan-fold, notch, perforated, tag, care label (outside wound)		
Media width	20 ~ 114mm (0.79" ~ 4.5")		
Media thickness	0.06 ~ 0.28 mm (2.36 ~ 11mil)		
Media core diameter	3.81mm / 76.2 mm (1.5"/3")		
Label length	5 ~ 11,430mm (0.20" ~ 450")		
Environment condition	<ul style="list-style-type: none"> •Operation: 0 ~ 40°C(32 ~ 104°F), 25~85% non-condensing •Storage: -40 ~ 60°C(-40 ~ 140°F), 10~90% non-condensing 		
Safety regulation	FCC Class A, CE Class A, RCM Class A, UL, cUL, TÜV, CCC, KC, BIS, BSMI, EAC, Argentina S mark, Mexico CoC, ENERGY STAR®		
Environmental concern	Comply with RoHS, WEEE		
Accessories	<ul style="list-style-type: none"> •Windows labeling software CDdisk •Quick start guide •USB port cable •Power cord 		
RTC & Buzzer	Standard		
Limited warranty	<ul style="list-style-type: none"> •Printer: 2 years •Print head: 25 km (1million inches) or 12 months which comes first •Platen: 50 km (2million inches) or 12 months which comes first 		
Factory option	<ul style="list-style-type: none"> •GPIO(DB15F)+ Parallel interface •Internal Bluetooth 5.0 MFi* 		
Dealer option	<ul style="list-style-type: none"> •Regular cutter (full cut guillotine cutter) •Heavy-duty cutter (full cut guillotine cutter) •Care label cutter •1" I.D. core media spindle 	<ul style="list-style-type: none"> •802.11a/b/g/n/ac Wi-Fi with Bluetooth 4.2 combo module (including slot-in housing)* •Peel-off kit •Internal rewinder kit (5" O.D.) 	
User option	<ul style="list-style-type: none"> •Basic cutter tray •Advanced cutter tray 	<ul style="list-style-type: none"> •Universal cutter tray •KP-200 Plus keyboard display unit 	



* Availability may vary by region.

MH241 and MH261 Series | Data Sheet

PREMIUM			
Model	MH241P	MH341P	MH641P
Resolution	8 dots/mm (203 DPI)	12dots/mm (300 DPI)	24 dots/mm (600 DPI)
Printing method	Thermal Transfer and Direct Thermal		
Max. print speed	356 mm (14")/second	305 mm (12")/second	152mm (6")/second
Max. print width	104mm (4.09")		
Max. print length	25,400 mm (1000")	11,430mm (450")	2540 mm (100")
Enclosure	Die-cast print mechanism and base with bi-fold metal cover with large clear media view window		
Physical dimension	276 mm (W) x 412mm (H) x 502 mm (D) 10.87" (W) x 16.22" (H) x 19.76" (D)		
Weight	18.93kg (41.73lbs)		
Label roll capacity	203.2 mm (8") O.D.		
Internal rewinder (full roll)	Standard (8" O.D.)		
Ribbon	600 m long, max. O.D.90mm, 1"core (ink coated outside or inside)		
Ribbon width	25.4 mm ~ 114.3mm (1"~ 4.5")		
Processor	32-bit RISC CPU		
Memory	<ul style="list-style-type: none"> •512MB Flash memory •256MB SDRAM •microSD Flash memory card reader for Flash memory expansion, up to 32 GB 		
Interface	<ul style="list-style-type: none"> •RS-232 •USB 2.0 (High speed mode) •Internal Ethernet, 10/100Mbps •USB host *2 (Front side), for scanner or PC keyboard •GPIO(DB15F)+Centronics (factory option) •Internal Bluetooth 5.0 MFi(factory option) •Slot-in 802.11a/b/g/n/ac Wi-Fi with Bluetooth 4.2 combo module (dealer option) 		
Power	<ul style="list-style-type: none"> •Internal switching power supply •Input: AC100-240V, 4-2A, 50-60Hz •Output: DC5V, 5A; DC24V, 7A; DC36V, 1.4A; Total 243W 		
LCD display/ Operation buttons	<ul style="list-style-type: none"> •Multi-language selectable •6 operation buttons •1 LED (with 2 LEDs Green & Red) 		
LCD	4.3" color display, 480 x 272pixel; Resistive touch screen		
Sensors	<ul style="list-style-type: none"> •Gap transmissive sensor (position adjustable) •Black mark reflective sensor (Bottom or Top black mark sensor switchable and position adjustable) •Head open sensor •Ribbon encoder sensor •Ribbon end sensor •Media near end sensor 		
Real time clock	Standard		
Internal font	<ul style="list-style-type: none"> •8 alpha-numeric bitmap fonts •Monotype Image@true type font engine with CG Triumvirate Bold Condensed scalable font 		
Barcode	1Dbarcode Code 39, Code 93, Code128UCC, Code128subsets A,B,C, Codabar, Interleave 2 of 5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC2(5) digits add-on, MSI, PLESSEY, POSTNET, RSS-Stacked, GS1DataBar, Code 11, China Post 2Dbarcode PDF-417, Maxicode, DataMatrix, QRcode, Aztec		
Font & barcode rotation	0, 90, 180, 270 degree		
Printer language	TSPL-EZD (Compatible to EPL, ZPL, ZPL II, DPL)		
Media type	Continuous, die-cut, black mark (Bottom side or top side black mark), fan-fold, notch, perforated, tag, care label (outside wound)		
Media width	20 ~ 114mm (0.79" ~ 4.5")		
Media thickness	0.06 ~ 0.28 mm (2.36 ~ 11mil)		
Media core diameter	3.81mm / 76.2 mm (1.5"/3")		
Label length	5 ~ 2,540 mm (0.20" ~ 100")		
Environment condition	<ul style="list-style-type: none"> •Operation: 0 ~ 40°C (32 ~ 104°F), 25~85% non-condensing •Storage: -40 ~ 60 °C (-40 ~ 140 °F), 10~90% non-condensing 		
Safety regulation	FCC Class A, CE Class A, RCM Class A, UL, cUL, TÜV, CCC, KC, BIS, BSMI, EAC, Argentina S mark, Mexico CoC, ENERGY STAR®		
Environmental concern	Comply with RoHS, WEEE		
Accessories	<ul style="list-style-type: none"> •Windows labeling software CD disk •Quick start guide •USB port cable •Power cord 		
RTC & Buzzer	Standard		
Limited warranty	<ul style="list-style-type: none"> •Printer: 2 years •Print head: 25 km (1 million inches) or 12 months which comes first •Platen: 50 km (2 million inches) or 12 months which comes first 		
Factory option	<ul style="list-style-type: none"> •GPIO (DB15F)+ Parallel interface •Internal Bluetooth 5.0 MFi* 		
Dealer option	•802.11a/b/g/n/ac Wi-Fi with Bluetooth 4.2 combo module (including slot-in housing)*		
User option	•KP-200 Plus keyboard display unit		



* Availability may vary by region.

WILUX PRINT AG
Unterfeldstrasse 5
CH-8340 Hinwil

Tel.: +41 (0)55 253 24 24
Fax: +41 (0)55 253 24 25

mail@wilux.ch
www.wilux.ch
www.labellingshop.com



wilux print
swissness
Ihr Partner für Etikettier- und Kennzeichnungslösungen

MH241 and MH261 Series | Data Sheet

Model	MH261T	MH361T
Resolution	8 dots/mm (203 DPI)	12 dots/mm (300 DPI)
Printing method	Thermal Transfer and Direct Thermal	
Max. print speed	305 mm (12")/second	254 mm (10")/second
Max. print width	168mm (6.61")	
Max. print length	14,732mm (580")	6,604 mm (260")
Enclosure	Die-cast print mechanism with large clear media view window	
Physical dimension	357 mm (W) x 313mm (H) x 514mm (D) 14.05" (W) x 12.32 (H) x 20.24" (D)	
Weight	17.8kg (39.24 lbs)	
Label roll capacity	208.3 mm (8.2") O.D.	
Internal rewinder (full roll)	Internal rewinder kit (5" O.D.)(dealeroption)	
Ribbon	450 m long, max. O.D.81mm, 1"core (Ink coated outside or inside)	
Ribbon width	50.8 mm ~ 178mm (2" ~ 7")	
Processor	32-bit RISC CPU	
Memory	<ul style="list-style-type: none"> •512MB Flash memory •256MB SDRAM •microSD Flash memory card reader for Flash memory expansion, up to 32 GB 	
Interface	<ul style="list-style-type: none"> •RS-232 •Parallel •USB 2.0 (High speed mode) •Internal Ethernet, 10/100 Mbps •USB host *2 (Front side), for scanner or PCkeyboard •GPIO(DB15F) (dealer option) •Slot-in 802.11a/b/g/n/ac Wi-Fi with Bluetooth 4.2 combo module (dealer option) 	
Power	Auto sensing power supply <ul style="list-style-type: none"> •Input: AC100-240V, 4-2A, 50-60Hz •Output: DC5V, 5A; DC24V, 7A; DC36V, 1.4A; Total 243W 	
LCDdisplay/ Operation buttons	<ul style="list-style-type: none"> •Multi-language selectable •6 operation buttons •1LED (with 2 LEDs Green & Red) 	
LCD	4.3" color display, 480 x 272pixel; Resistive touch screen	
Sensors	<ul style="list-style-type: none"> •Gap transmissive sensor (Position adjustable) •Black mark reflective sensor (Bottom black mark sensor, Position adjustable) •Head open sensor •Ribbon encoder sensor •Ribbon end sensor 	
Real time clock	Standard	
Internal font	<ul style="list-style-type: none"> •8 alpha-numeric bitmap fonts •Monotype Image@true type font engine with CG Triumvirate Bold Condensed scalable font 	
Barcode	1Dbarcode Code 39, Code 93, Code128UCC, Code128subsets A.B.C, Codabar, Interleave 2 of 5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC2(5) digits add-on, MSI, PLESSEY, POSTNET, RSS-Stacked, GS1DataBar, Code 11, China Post 2Dbarcode PDF-417, Maxicode, DataMatrix, QRcode, Aztec	
Font & barcode rotation	0, 90, 180, 270 degree	
Printer language	TSPL-EZD(Compatible to EPL, ZPL, ZPL II, DPL)	
Media type	Continuous, die-cut, black mark (Bottom side black mark only), fan-fold, notch (outside wound)	
Media width	50.8 ~ 172.7mm (2"~ 6.8")	
Media thickness	0.06 ~ 0.268 mm (2.36~ 11.02mil)	
Media core diameter	3.81mm / 76.2 mm (1.5"/3")	
Label length	10~14,732mm (0.39"~ 580")	10~ 6,604 mm (0.39"~ 260")
Environment condition	<ul style="list-style-type: none"> •Operation: 0~40 °C(32 ~104°F), 25~85% non-condensing •Storage: -40 ~60 °C(-40 ~140°F), 10~90% non-condensing 	
Safety regulation	FCC Class A, CE Class A, RCM Class A, UL, cUL, TÜV, CCC, KC, BIS, BSMI, EAC, Argentina S mark, Mexico CoC, ENERGY STAR®	
Environmental concern	Comply with RoHS, WEEE	
Accessories	<ul style="list-style-type: none"> •Windows labeling software CD disk •Quick start guide •USB port cable •Power cord 	
Limited warranty	<ul style="list-style-type: none"> •Printer: 2 years •Print head: 25 km (1million inches) or 12 months which comes first •Platen: 50 km (2 million inches) or 12 months which comes first 	
Dealer option	<ul style="list-style-type: none"> •GPIO (DB15F) •Heavy duty cutter •802.11a/b/g/n/ac Wi-Fi with Bluetooth 4.2 combo module (including slot-in housing)* •Peel-off kit •Internal rewinder kit (5" O.D.) 	
User option	•KP-200 Plus keyboard display unit	



* Availability may vary by region.
Product models and specifications are subject to change without notice.

WILUX PRINT AG
Unterfeldstrasse 5
CH-8340 Hinwil

Tel.: +41 (0)55 253 24 24
Fax: +41 (0)55 253 24 25

mail@wilux.ch
www.wilux.ch
www.labellingshop.com



wilux print
swissness
Ihr Partner für Etikettier- und Kennzeichnungslösungen